

Wheeler Engineering

Delta Series AR-15 Adjustable Receiver Link

The AR-15 Adj. Receiver Link will quickly become your go-to-tool when performing routine cleaning operations or making those anticipated performance upgrades. The Adjustable Receiver Link is designed to maintain and secure the opened position of your AR-10 or AR-15 upper and lower assembly. The kit comes with one upper link and two threaded lower links (one short, one long) to provide a total adjustment of approx. 3/4". The upper link utilizes an integral pin to engage the upper receiver and the threaded lower portion utilizes the existing lower takedown hole and pin.

- The short lower link provides a minimum opened position of 1.2" pin to pin, enough room to insert a bore guide, and the maximum opening is 1.5" from pin to pin.
- The longer threaded link will provide a minimum opening of 1.4" and a maximum opening of 1.8" from pin to pin.
- All components are constructed of steel and corrosion resistant. The precise tolerances and durable materials will ensure years or reliable service from this handy device.

Warnings:

Standard Warning Information about safety equipment and gun safety.

Usage Instructions

1. Determine which threaded lower link is needed for your particular application and thread it into the Upper Link. A minimum of three revolutions of thread engagement is recommended.
2. Position your AR lower into a secure holding device. We recommend the Delta Series AR-15 Mag Well mounted to a Tipton Best Gun Vise. **(Photo)**
3. Depress the rear takedown pin and open the receiver forward.
4. Install the Receiver Link engaging the hinge pin boss of your AR Upper Receiver. **(Photo)**
5. Make the desired length adjustments to the Lower Link and align it with your lower receiver takedown pin hole and press the pin fully through the lower. **(Photo)**